



## AXT405 GMH Black

### Features

- Nitrocellulose based industrial lacquer
- Can be used as a guide coat
- Quick drying
- Low gloss
- Good coverage
- Easy to apply
- Ready for use

### Product

GMH Black

### Colour








Black

### Substrates


- Subframes, beneath mudguards etc.

<p><b>Surface preparation</b></p> <ul style="list-style-type: none"> <li>• Clean with AXT126 Wax and Grease Remover.</li> </ul>
---

<b>Product Preparation</b>	Ready for use, shake well before use.
----------------------------	---------------------------------------

	<b>Working process</b>	<b>Nitrocellulose lacquer and as a guide coat</b>
	<b>Substrates:</b>	Subframes, beneath mudguards etc.
	<b>Pretreatment / Cleaning:</b>	Clean with AXT126 Wax and Grease Remover
	<b>Application:</b>	Use recommended respirators. Refer to relevant Safety Data Sheet (SDS)
		Ready for use, shake well before use
		1.6 – 1.8 mm 300 – 400 kPa 3 coats = approx. 10 microns
		1.8 – 2.0 mm 300 – 400 kPa 2 – 3 coats = approx. 10 microns
		5 minutes / 20°C between coats
		10 minutes / 20°C

<b>Flashpoint:</b>	Approx. -5 °C
<b>Raw Material:</b>	Nitrocellulose based resins
<b>Specific Gravity:</b>	0.8 g/L
<b>Approx. Coverage:</b>	6.5 m <sup>2</sup> /L at 10 microns DFT
<b>Cleaning of Equipment:</b>	Clean after use with AXT350 Multi Acrylic Thinner
<b>Important Remarks:</b>	For professional use only <b>Notes:</b> 1. As AXT405 GMH Black is a fast drying Nitrocellulose based lacquer, there may be a tendency for this product to bloom or blush in cold weather 2. Not for exterior exposure
This data relates only to the material designated herein and does not apply to use in combination with any other material or any process. The data is not to be considered as a warranty or quality specification and we assume no liability in connection with its use.	

<b>Note on safety:</b>	
	Please consult the Safety Data Sheet. It is strongly recommended to use appropriate personal protection equipment during application.
	Observe the precautionary notices displayed on the container.

## Information

The information provided herein corresponds to our knowledge on the subject at the date of its publication. This information may be subject to revision as new knowledge and experience becomes available. The data provided fall within the normal range of product properties and relate only to the specific material designated; these data may not be valid for such material used in combination with any other materials or additives or in any process, unless expressly indicated otherwise. The data provided should not be used to establish specification limits or used alone as the basis of design; they are not intended to substitute for any testing you may need to conduct to determine for yourself the suitability of a specific material for your particular purposes. Since Axalta cannot anticipate all variations in actual end-use conditions Axalta makes no warranties and assumes no liability in connection with any use of this information. Nothing in this publication is to be considered as a license to operate under or a recommendation to infringe any patent rights.

This Technical Data Sheet supersedes all previous issues.

Copyright© 2016, Axalta Coating Systems, LLC and all affiliates. All rights reserved. The Axalta logo, Axalta™ Axalta Coating Systems™ and all products denoted with ™ or © are trademarks or registered trademarks of Axalta Coating Systems, LLC and its affiliates. Axalta trademarks may not be used in connection with any product or service that is not an Axalta product or service.