



3919SC™ KLENE-SOL® CLEANING SOLVENT



GENERAL

DESCRIPTION

3919SC Klene-Sol® is a cleaning solvent specifically designed for initial surface preparation before painting. 3919SC works well on the following difficult to remove elements: wax, grease, silicone, dirt, tar, tree sap, insect remnants, road film and pin stripe adhesives.

The products referenced herein may not be sold in your market. Please consult your distributor for product availability.



MIXING

COMPONENTS

3919SC Klene-Sol®

MIX RATIO

Ready to use



APPLICATION

SUBSTRATES

- Unsanded substrates
- OEM finishes
- Cured, repainted surfaces

Do not use on unprimed plastic or fiberglass substrates due to possible static buildup, which may cause a flash fire.

SURFACE PREPARATION

Clean surface with mild detergent and water.

APPLICATION

- For spot cleaning surfaces prior to sanding only.
- VOC regulations require the use of atomizing spray bottles for the application of 3919SC.
- Wipe surface to loosen and lift the contaminants; follow immediately by wiping thoroughly with a clean dry cloth.

Tips for Success

- Do not allow 3919SC to dry before removing from the surface. For hard to remove contaminants, reapply and allow 3919SC to sit on the surface for a few minutes without drying, then wipe to loosen contaminants.
- Clean hard to remove tar and grime with a mild detergent prior to using 3919SC. Use a clean cloth for wiping 3919SC.



PHYSICAL PROPERTIES

All Values Ready To Spray

Max. VOC (LE):	770 g/L
Max. VOC (AP):	770 g/L
Flash Point:	See SDS

VOC REGULATED AREAS

These directions refer to the use of products which may be restricted or require special mixing instructions in VOC regulated areas. Follow mixing usage and recommendations in the VOC Compliant Products Chart for your area.

SAFETY AND HANDLING

For industrial use only by professional, trained painters. Not for sale to or use by the general public. Before using, read and follow all label and MSDS / SDS precautions. If mixed with other components, mixture will have hazards of all components.

Ready to use paint materials containing isocyanates can cause irritation of the respiratory organs and hypersensitive reactions. Asthma sufferers, those with allergies and anyone with a history of respiratory complaints must not be asked to work with products containing isocyanates.

Do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves.

Revised: October 2016

In the United States:
1.855.6.AXALTA
cromax.us

In Canada:
1.800.668.6945
cromax.ca

