



SURFACE KLEAN A-3970S™ / A-3990S™ SURFACE CLEANER



GENERAL

DESCRIPTION

A surface cleaner in an aerosol format that leave no surface residue. The unique solvent blend is formulated to remove wax, grease, silicone, dirt, tar, insect remnants, sanding dust and compound sludge prior to topcoat.

The products referenced herein may not be sold in your market. Please consult your distributor for product availability.



MIXING

COMPONENTS

Surface Klean A-3970S™ Surface Cleaner - Low Temperature
Surface Klean A-3990S™ Surface Cleaner - High Temperature

MIX RATIO

Ready to use



APPLICATION

SUBSTRATES

- Sanded substrates
- OEM finishes
- Cured, repainted surfaces
- Sanded primers

Do not use on unprimed plastic or fiberglass substrates due to possible static buildup, which may cause a flash fire.

SURFACE PREPARATION

Use Surface Klean A-3970S™ / A-3990S™ to remove wax, grease, silicone, dirt, tar, insect remnants, sanding dust and compound sludge prior to topcoat.

APPLICATION

- Apply A-3970S™ / A-3990S™ to substrate to remove wax, grease, silicone, dirt, tar, insect remnants, sanding dust, and compound sludge prior to topcoat.
- Wipe the surface while it is still wet to loosen and lift the contaminant from the substrate.
- Follow immediately by wiping the surface thoroughly dry with a clean Sontara® cloth (E-4142 or E-4143).
- For hard to remove surface contamination, repeat the previous process steps.

Tips for Success

- Do not allow A-3970S™ / A-3990S™ to dry on the surface. If this does occur, simply re-spray and wipe dry. Use a clean cloth for applying and wiping A-3970S™ / A-3990S™.
- Do not use A-3970S™ / A-3990S™ on unprimed plastic or fiberglass substrates, due to possible static buildup; the use of this surface cleaner on unprimed plastic or fiberglass may cause a flash fire.
- Do not puncture, incinerate, burn or store above 120°F.



DRY TIMES

Flash Between Coats: 10-15 minutes
 Dust Free: 30 minutes at 70°F (20°C)



PHYSICAL PROPERTIES

VOC (lbs./gallon in RTS Can):	A-3970S™	A-3990S™
AP (As Supplied):	6.2 lbs/gal	6.4 lbs/gal
Avg. Gallon Weight:	6.37 lbs/gal	6.59 lbs/gal
Avg. Weight % Volatiles:	100%	100%
Avg. Weight % Exempt Solvent:	0.0%	0.0%
Avg. Weight % Water:	0.0%	0.0%
Avg. Volume % Exempt Solvent:	0.0%	0.0%
Avg. Volume % Water:	0.0%	0.0%
Flash Point:	See SDS	

VOC REGULATED AREAS

These directions refer to the use of products which may be restricted or require special mixing instructions in VOC regulated areas. Follow mixing usage and recommendations in the VOC Compliant Products Chart for your area.

SAFETY AND HANDLING

For industrial use only by professional, trained painters. Not for sale to or use by the general public. Before using, read and follow all label and MSDS/SDS precautions. If mixed with other components, mixture will have hazards of all components.

Ready to use paint materials containing isocyanates can cause irritation of the respiratory organs and hypersensitive reactions. Asthma sufferers, those with allergies and anyone with a history of respiratory complaints must not be asked to work with products containing isocyanates.

Do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves.

Revised: January 2019

In the United States:
1.855.6.AXALTA
cromax.us

In Canada:
1.800.668.6945
cromax.ca

