

Low VOC Chart



For the District of Columbia

Motor Vehicle and Mobile Equipment Non-Assembly Line Coating Operations - Title 20, Chapter 7 - Section 718

Revised: July 2021

Effective: May 9, 2016

Surface Preparation - VOC Limit: 25 g/L (0.21 lbs./gal.)

CODE	DESCRIPTION	REMARKS	MIX RATIO	APPLIED VOC	
1760	Cleaner		Ready To Use	24 g/L	
2010	Cleaner		Ready To Use	0 g/L	
2040	Cleaner		Ready To Use	0 g/L	
2571	Cleaner		Ready To Use	24 g/L	
4040	Cleaner		Ready To Use	0 g/L	
8007	Cleaner		Ready To Use	0 g/L	
281	Aerosol Surface Cleaner	*Note in Footer	Ready To Use	779 g/L	

Primer - VOC Limit: 250 g/L (2.1 lbs./gal.)

CODE	DESCRIPTION	REMARKS	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)
6811	Gray Primer		4:1	6896	-	250 g/L
922	Gray Primer		1:1	2010	-	250 g/L
941	Polyester Primer		4:1	9498	-	250 g/L

Primer Sealer - VOC Limit: 250 g/L (2.1 lbs./gal.)

CODE	DESCRIPTION	REMARKS	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)
6711	Gray Epoxy Primer Sealer		2:1	6796	-	250 g/L
6713	Charcoat Epoxy Primer Sealer		2:1	6796	-	250 g/L

Single Stage Topcoats - VOC Limit: 340 g/L (2.8 lbs./gal.)

CODE	DESCRIPTION	REMARKS	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)
2513	Satin Black		4:1	2696	-	340 g/L
2713	Flat Black		4:1	2696	-	340 g/L
2813	Eurocoat Black		4:1:2	2896	8025/8050/8075/8100	340 g/L
2817	Eurocoat White		4:1:2	2896	8025/8050/8075/8100	340 g/L

Clearcoat - VOC Limit: 250 g/L (2.1 lbs./gal.)

CODE	DESCRIPTION	REMARKS	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)
2210	Ultra Auto Clearcoat		4:1	2294	-	250 g/L
2594	Satin Urethane Clearcoat		4:1	2696	-	250 g/L
2610	Super Pro Clearcoat		4:1	2696	-	250 g/L
2623	Flat Clearcoat		4:1	2696	-	250 g/L

*Aerosol surface cleaning allowed if 160 ounces or less is used per day per facility.

Additional additives/components may be used, please consult TDS for usage and recommendations.

All VOC (LE) values listed are maximum Ready-to-Spray in pounds per gallon.