## **Standox® VOC Compliance Chart**

## Automobile Refinish Coatings

## **Canadian National Rule**

Canada Gazette Part II, Volume 143, No 14

Revised: March 18, 2020



Description	Article #	Compliant Rules				Applied VOC g/L	Remarks
Surface Preparation VOC Limit = .42 lbs/gal (50 g/L)							
130™ Axalta Cleaner	130					0	
200™ Silicone Remover Slow	200	Used as a spot cleaner only in a hand-held spray bottle prior to sanding				779**	Only for spot cleaning; must use hand held spray bottle
205A™ Silicone Remover Spray	205A	Aerosol cleaners (non-refillable) *					Non-refillable aerosol *
220™ Axalta Silicone Remover Low VOC 225™ Bug & Tar Remover	220 225	Used as a spot cleaner only in a hand-held spray bottle prior to sanding				20 347**	Only for spot cleaning; must use hand held spray bottle
265™ Axalta Plastic Cleaning Paste	265	Source as a spot organismonity in a manuficial spray bottle prior to samuling				24	Only for spot cleaning; must use hand held spray bottle
275™ Plastic Cleaning Solvent	275	Used as a spot cleaner only in a hand-held spray bottle prior to sanding					Only for spot cleaning; must use hand held spray bottle
Standoflex® Low VOC Plastic Cleaner	16010	· · · · · · ·				13	
Standoflex® Thinners 11100	16160	Used as a spot cleaner only in a hand-held spray bottle prior to sanding				859**	Only for spot cleaning; must use hand held spray bottle
Standohyd® VOC Cleaner 25	16178					25	7 7 7
Standox® Silicone Remover Antistatic	16203	Used as a spot cleaner only in a hand-held spray bottle prior to sanding				776**	Only for spot cleaning; must use hand held spray bottle
Standox® Silicone Cleaner (Aerosol)	16208	Aerosol cleaners (non-refillable) *					Non-refillable aerosol *
Description	Article #	Mix Ratio	Hardener	Thinner/ Additive	Addtl Product	Max Applied VOC (LE) g/L	Remarks
Pretreatment VOC Limit = 5.5 lbs/gal (660 g/L)							
Standox® 1K Primer Red-Brown (Aerosol)	14696	Ready to Use	N/A	N/A	N/A	N/A*	Non-refillable aerosol *
Standox® Low VOC Etch Primer	16189	2:1	16190	N/A	N/A	660	
Standox® 1K Primer (Aerosol)	16228	Ready to Use	N/A	N/A	N/A	N/A*	Non-refillable aerosol *
Axalta® Pretreatment Wipes	PS4000™	Ready to Use	N/A	N/A	N/A	660	
Primer Surfacer VOC Limit = 2.1 lbs/gal (250 g/L)							
Standox® PF Filler	16220/16221	5:1+10-20%	PF Hardeners	16215, 16224, 16225	N/A	250	
Standox® PF Filler w/2K Plasticiser	16220/16221	5:1 +10-20%	PF Hardeners	16215, 16224, 16225	+15% 15260	250	15260 must be added before hardener.
Standox® 1K Waterborne Primer Surfacer	16231	1 +5-15%	N/A	80188	11370 13200	250	13200 must be added before nardener.
Primer-Sealer VOC Limit = 2.8 lbs/gal (340 g/L)	10201	1 10 1070	1971	00.00		200	
Standox® PF Sealer	16222/16223	4:1+30%	PF Hardeners	16224, 16225	N/A	340	
Standox® PF Sealer w/2K Plasticiser	16222/16223	4:1+30%	PF Hardeners	16224, 16225	+15% 15260	340	15260 must be added before hardener.
Standox® 2K EP Primer (Aerosol)	16181	Ready to Use	N/A	N/A	N/A	N/A*	Non-refillable aerosol *
Colour Coating VOC Limit = 3.5 lbs/gal (420 g/L)							
Standoblue® Basecoat	See Price List	10-30%	N/A	19302, 19303, 19304	N/A	420	
Standoblue® Basecoat	See Price List	+0-10% +10-30%	17400	19302, 19303, 19304	N/A	420	
Description	Article #	Mix Ratio	Hardener	Thinner/ Additive	Addtl Product	Max Applied VOC (LE) g/L	Remarks
Clear Coating VOC Limit = 2.1 lbs/gal (250 g/L)							
Standocryl® Clear PFC 20	16211	2:1+15%	PF Hardeners	16215	N/A	250	
Standocryl® Clear PFC 20 w/2K Plasticiser	16211	2:1+15%	PF Hardeners	16215	+10-15% 15260	250	15260 must be added before hardener.
Standocryl® Clear PFC 30	16216	2:1+5%	PF Hardeners	16215	N/A	250	
Standocryl® Clear PFC 30 w/2K Plasticiser	16216	2:1+10%	PF Hardeners	16215	+10-15% 15260	250	15260 must be added before hardener.
Standocryl® Clear PFC Air Dry	16218	4:1 +20%	PF Hardeners	16215	N/A	250	
Standocryl® Clear PFC Air Dry w/2K Plasticiser	16218	4:1 +20%	PF Hardeners	16215	+10% 15260	250	15260 must be added before hardener.
Uniform Finish Coating VOC Limit = 4.5 lbs/gal (540 g/L)							10200 mast 50 dadod boloto maldonor.
andox® 2k Smart Blend Plus wPFC 20 (16211) 16174 See TDS 1206 for compliant mixing recommendations						540	
Standox® 2k Smart Blend Plus w/PFC 20 (16211) Standox® 2k Smart Blend Plus w/PFC 30 (16216)	16174	See TDS 1206 for complian				540 540	
Standoblue® Color Blend	19310/19311	+5-10%	N/A	19302, 19303, 19304	+5% 18316	540	
Standoblue® Color Blend	19310/19311	+0-5%	N/A	18316	N/A	540	
Standoblue® Basecoat	19310	4:1+20-30%	19310	19302, 19303, 19304	N/A	540	
Standoblue® Basecoat	19310	4:1+20-30%	19310	19302, 19303, 19304	N/A	540	
Standoblue® Basecoat	19310	1:1+10%	19310	Mix 199	N/A	540	
Adhesion Promoter VOC Limit = 7.0 lbs/gal (840 g/L)						0.0	
Standoflex® Plastic Primer Silver (Aerosol)	14408	Aerosol	N/A	N/A	N/A	N/A*	Non-refillable aerosol *
Other Products							
Standox® Additive Blue	16255	See TDS	l N/A	N/A	N/A	420	
Standox® Additive Maroon	16256	See TDS	N/A N/A	N/A N/A	N/A	420	
Standox® Additive Majoori	16257	See TDS	N/A	N/A	N/A	420	
Standox® Additive KA679 Bright Red	16679	See TDS	N/A	N/A	N/A	420	
* Non-refillable aerosols are excluded from Automotive Refinish Regulation			_				

<sup>\*</sup> Non-refillable aerosols are excluded from Automotive Refinish Regulations

For complete product usage and mixing recommendations, see the product specific technical data sheet located on www.standoxna.com.

Copyright © 2020 Axalta Coating Systems. Standox® and all products designated with TM or ® are trademarks or registered trademarks of Axalta Coating Systems for its brands of refinish systems. All rights reserved.

<sup>\*\*</sup> Excluded product from the Automotive Refinish Regulations