

# Low VOC Chart

For Utah (See note in footer for applicability)  
Rule R307-354 Automotive Refinish Coatings



Effective: July 1, 2014

Revised: Jan 2020

Compliant Aerosol Coating Products   Rule 307-354			
CODE	DESCRIPTION	CODE	DESCRIPTION
402-01™	Gloss Trim Black	421-25™	Red Oxide Primer
402-02™	Flat Trim Black	421-26™	Beige Primer
402-03™	Semi Gloss Trim Black	441-37™	Nason® Fill-In Can
402-11™	Gloss White	491-40™	Self-Etch Primer
403-00™	Clearcoat	492-51™	Undercoating

Cleaning Solvents   VOC Limit N/A				
CODE	DESCRIPTION	REMARKS	MIX RATIO	APPLIED VOC
105™	Gun & Equipment Cleaner		Ready To Use	650 g/L
106™	Cleaner		Ready To Use	528 g/L
107™	Gun & Equipment Cleaner		Ready To Use	25 g/L
108™	Low HAP Cleaner		Ready To Use	472 g/L
130™	Cleaner		Ready To Use	0 g/L
139™	Bug & Tar Remover		Ready To Use	347 g/L
200™	Silicone Remover Slow		Ready To Use	778 g/L
205A™	Silicone Remover (Aerosol)		Ready To Use	760 g/L
210™	Silicone Remover Water		Ready To Use	167 g/L
220™	Silicone Remover Low VOC		Ready To Use	25 g/L
225™	Bug & Tar Remover		Ready To Use	347 g/L
275™	Plastic Cleaning Solvent		Ready To Use	862 g/L
265™	Plastic Cleaning Paste		Ready To Use	25 g/L
715™	Sanding Paste		Ready To Use	n/a
441-05™	Wax & Grease Remover		Ready To Use	778 g/L
441-75™	Cleaner		Ready To Use	779 g/L
481-75™	Cleaner	Aerosol	Ready To Use	785 g/L

Pretreatment Coating VOC Limit   660 g/L (5.5 lb./gal)					
CODE	DESCRIPTION	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)*
491-55™	Chrome-Free Etch Primer	2:1	-	441-55™	660 g/L

Adhesion Promoter VOC Limit   540 g/L (4.5 lb./gal)					
CODE	DESCRIPTION	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)*
491-50™	Adhesion Promoter	-	-	-	540 g/L

Primer VOC Limit   250 g/L (2.1 lb./gal)					
CODE	DESCRIPTION	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)*
421-1X	Primer (⚠ - Note in footer)	4:1	483-03™	-	250 g/L
421-30™	Primer Surfacer	1:1	-	441-60™	250 g/L

Primer Sealer VOC Limit   250 g/L (2.1 lb./gal)					
CODE	DESCRIPTION	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)*
421-1X	Sealer (⚠ - Note in footer)	3:1:2	483-03™	401-X5	250 g/L
491-1X	Primer Sealer	2:1	483-01™ / 483-02™	-	250 g/L

Single Stage Coating VOC Limit | 340 g/L (2.8 lb./gal)  
Additional additives may be used. Consult technical data sheet for usage and compliance.

CODE	DESCRIPTION	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)*
IS	Ful-Thane® Single Stage Topcoat	4:1:2	483-56™	441-6X	340 g/L
412-01™	Ful-Thane® Single Stage Topcoat	4:1:2	483-56™	441-6X	340 g/L
412-50™	Ful-Thane® Single Stage Topcoat	4:1:2	483-56™	441-6X	340 g/L

Color Coating VOC Limit | 420 g/L (3.5 lb./gal)  
Additional additives may be used. Consult technical data sheet for usage and compliance.

CODE	DESCRIPTION	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)*
IR	Ful-Base® Basecoat	1:1	‡ See Footer	441-6X	420 g/L

Clear Coating VOC Limit   250 g/L (2.1 lb./gal)					
CODE	DESCRIPTION	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)*
462-00™	Clearcoat	4:1	483-84™ / 483-85™	-	250 g/L
468-00™	Clearcoat	4:1	483-84™ / 483-85™	-	250 g/L
468-00™	Clearcoat	3:1	483-86™	-	250 g/L
476-00™	Clearcoat	2:1	483-64™ / 483-65™	-	250 g/L

Other components that may be used (list is not all-inclusive). Consult technical data sheet for usage and compliance.

CODE	DESCRIPTION	CODE	DESCRIPTION
401-22™	Low VOC Gloss Enhancer	441-83™	Low VOC Flow Additive
483-13™	Gloss Additive	483-99™	Low VOC Sunshield
483-14™	Gloss Additive	495-01™	Fisheye Eliminator
483-18™	Accelerator	495-02™	Topcoat Additive

R307-354 Applicability: Applies to sources in Box Elder, Cache, Davis, Salt Lake, Tooele, Utah, and Weber Counties; facilities that use a combined 20 gallons of coatings and solvents per year.

‡ Optional Activation: Add 1 oz. 483-56™ RTS quart

⚠ - Refers only to products 421-10™, 421-11™ & 421-12™  
An Axalta Coating Systems Brand

© 2016 Axalta Coating Systems, LLC and all its affiliates. All rights reserved.

X = 0, 1, 2, 6, 8

\*Less Water, Less Expense™

483-56 AXALTA

nasonfinishes.com